

Tube squaring machines Protem® SL

Technical Features

Machining capacity

SL30:	3 – 30 mm AD (0,188" - 1,181")
SL60:	13 – 63,5 mm AD (0,511" - 2,500")
SL120:	50 – 120 mm AD (1,968" - 4,724")

The SL-series has been especially designed to square tubes, fittings and tees on most metal pipes and tubes including stainless steel. The clearances, capacities and designs have been engineered along with the endusers industries. The maximum wall thickness is 8 mm above that we suggest the machines of the SE-series.



- Perfect squaring of elbows, fittings and micro fittings in connection with the short clamping head
- Time saving thanks to the quick changing of collets and short heads
- Small dimensions
- Ideal for clean room application
- Can be used as a portable tool or bench mounted
- Manual feed with button
- High capacity electric drive 1050 W (pneumatic drive on request)

Machine is delivered with:

- Electric drive
- 1 tool holder plate
- 1 tool insert holder 90
- 1 cutting insert
- Keys and screws
- Operating manual

WITHOUT EXPANSION COLLET!

Subject to modification without prior notice. Its content is confidential, this document is unique and is PROTEM property, it shall not be corrected, duplicated or modified without the written agreement of PROTEM.
The content refers exclusively to the sales and delivery conditions of the seller.

Page 1 / 1